TECHNICAL DATASHEET
PART NO: BCS1220



Ref No: BCS1YE00905

DESCRIPTION :


EIB/KNX Cable – 1 pair (2-core twisted pair) with 0.8 mm solid bare copper conductors, overall shielded, LSZH green sheath, designed for KNX/EIB building automation systems

APPLICATION :

Suitable for KNX (EIB) bus systems, EHS, building automation system.

CONSTRUCTION :

Cores	1 Pair (2 Core)
Section	0.8mm
Conductor Material	Solid Bare Copper
Insulation	Polyethylene (PE)
Colour	Black, Red
Lay Up	2 Cores twisted to a pair
Wrapping	Polyethylene terephthalate foil
Screen (100% Coverage)	Aluminium/ Polyester
Drain Wire	Solid Tinned Copper Wire
Rip Cord	Nylon Yarn
Sheath Material	Low Smoke Zero Halogen (LSZH/ FRNC)
Sheath Color	Green RAL 6018
Standard Put Up Length	305, 500 meters



PHYSICAL & MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-25°C to +75°C
Nominal Cable Weight (kg/km)	40
Nominal Insulation Thickness (mm)	0.3
Nominal Sheath Thickness (mm)	1.2
Nominal Overall Diameter (mm)	5.10
Min. Bend Radius (install) (mm)	56
Max. Pull Tension (N)	52

ELECTRICAL CHARACTERISTICS

Max. Mutual Capacitance	100 pF/m
DC Resistance per core @ 20°C	38Ω/km
Insulation Resistance @ 20°C	102 MΩ/km (min)
Max. DC Loop (Ω/km)	73.6
Inductance	0.78 µH/m
Operating Voltage	300 V (Vrms)

TECHNICAL DATA & STANDARD REFERENCES

(BS) EN 50290-2
IEC 60754- 1 & 2, IEC 60228
IEC 61034, IEC 60332-3-24
UL 1685
RoHS Directives

BELFAST ACCREDITED BY :

www.belfastcables.co.uk | info@belfastcables.co.uk
Belfast Cables UK Solutions Ltd | 71–75, Shelton Street Covent Garden, London WC2H 9JQ, United Kingdom
Disclaimer: Information is believed to be accurate but may contain errors. Specifications may change without notice.

COMPANY PROFILE